

Applikations

- ... labels and tags for the chemical industry
- ... Optimised logistics with colour codes
- ... "eye catcher" on price tags with colour

Meets GHS regulations Pharmaceutical labels - now in 2 colour




OPTIONAL REWINDER



- **ROBUST METAL CASE**
Ideally suited for the rough industrial daily routine
- **COMPACT DESIGN**
SMALL FOOTPRINT
- **EASY HANDLING**
OF THE CONSUMABLES

- **PROCESS INTEGRATION**
VIA SPS-CONTROL
- **USB+ETHERNET AS**
STANDARD EQUIPMENT
- **SAP- AND AS/400-COMPATIBLE**
Supports PCL5e+Jetcaps and LAN-IPDS

The logiJET TC8 is an 8-inch thermal transfer printer that is perfect for industrial applications. The print engine is equipped with two print modules which can be loaded with different colours. The printer is PCL5e-compatible and can thus be operated like a laser printer. In this way it is not necessary to put up with adaptations and power drains at SAP-applications or in the process of changing from laser printer to a thermal printer.




Print Engine

Print technology	Thermotransferdruck harmonic (history-controlled flat head technology)	
Controller	MPC 5.4 with INTEL XScale PXA255 CPU (200-MHz-RISC-Processor)	
Print speed	up to 150 mm/s up to 6 inch/s	
Resolution	300 dpi x 300 dpi	
Lifetime print head	Transfer up to 50.000 m	
Power supply	AC 100 - 120, 200 - 240 V, 50/60 Hz	
Dimensions (BxTxH in mm)	389 x 420 x 430	
Weight (without cutter)	21 kg	
Environment	rel. h. (n.-kond.) temp.	45 - 75 % 5 - 35°C
Interfaces	Serial <i>optional</i> Parallel LAN	USB <i>RS232/RS422</i> IEEE 1284 Ethernet-Interface 10/100 MBit, bi-direktional (TCP/IP)
Memory	RAM Flash	64 MB 16 MB
Display	graphic Display, 128x64 Punkt, with backlight	

MPC 5.4 High-End Print-Controller

Emulations	HP PCL 5c MICROPLEX IDOL Epson FX-80 Datamax Express	IBM Proprinter Diablo 630 ZPLII EPL CUPS-Raster
Optional Emulations	Printronix IGP PGL, TIFF µ Postscript	Magnum Code V IPDS Kyocera Prescribe II <i>(more Barcodes on request)</i>
1D-Barcodes	EAN 8, 13, 128, add on 2/5 3-stroke Datalogic 2/5 3-stroke Matrix Codabar Royalbar Planet	Jetcaps (HP/SAP) Code 39 128 MSI UPC A, E Postnet, KIX USPS One Code
2D-Barcodes	USD5 Aztec-Code	UPS-Maxicode Datamatrix PDF-417 <i>(more Barcodes on request)</i>
Funktions	Format splitting in several subformats by command	
	Integrated form management up to 12 MB flash for forms and fonts inside the printer	
Optional Functions	Status-out <i>gives notice of each correctly printed page via interface</i>	
	SPS-control <i>integration of the printer into production lines is possible, controlled by SPS-interface.</i>	

Paper Path



Feeder/Stacker

Input	continuous	sensor for black mark and label gap (reflection and transmissive) external from roll external, e.g. fanfold
Output	single job	tear-off <i>option: cutter</i> tear-off <i>option: cutter</i>

Media

Size	width: min. 100 mm max. 228 mm printable: 219 mm	
Thickness	0,14 mm - 0,25 mm	
Ribbon	core diameter ribbon length coated side width	1 inch (25.4 mm) max. 450 m outside max. 220 mm
Unwinder (optional)		
Media Width	Breite: min. 100 mm max. 220 mm	
Thickness	0,14mm - 0,25 mm	
Roll Diameter	max. 203 mm with 3" core	
Core Diameter	3 inch (76,2 mm)	